



WeatherTek® STP

Advanced Polymer Sealant

PART OF THE WEATHERTEK SYSTEM



Aggressive Adhesion To Common Construction Substrates

WeatherTek® STP Advanced Polymer Sealant is a high-performance, moisture-curing sealant designed for professional construction use. It provides superior adhesion, flexibility, and long-term weather resistance on a wide range of materials.



Key Features & Applications

- Excellent UV and weather resistance
- Strong adhesion to most materials
- Paintable once cured
- Low-VOC, solvent-free
- Window & door sealing
- Roofing, trim, siding joints
- Masonry and flashing penetrations
- Housewrap and underlayment seams

Installation Guidelines

- Surfaces must be clean, dry, and free from oil, dust, and contaminants
- Cut nozzle to desired bead size and puncture inner seal
- Apply with standard caulking gun
- Tool within 10 minutes of application
- Paintable in 2 hours

Packing & Storage

- Store between 40°F and 80°F
- 12-month shelf life (unopened)



10.1 FL. OZ. Cartridge

12/case, 108 cases/pallet



PART OF THE WEATHERTEK SYSTEM

WeatherTek STP is eligible for a 20-Year WeatherTek System Warranty when installed with approved WeatherTek components.

Visit [weathertekbp.com](https://www.weathertekbp.com) for details



WeatherTek® STP

Advanced Polymer Sealant

PART OF THE WEATHERTEK SYSTEM



Specifications:

WeatherTek® STP meets or exceeds the requirements of ASTM C920 Type S, Grade NS, Class 35, Use NT, G, A, M, O. AAMA 714: Specification for Liquid Applied Flashing used to Create a Water-Resistive Seal around Exterior Wall Openings in Buildings.

Approximate* Linear Feet/Coverage Per 10.1 FL. OZ. Cartridge

		WIDTH							
		1/8"	1/4"	3/8"	1/2"	5/8"	3/4"	7/8"	1"
DEPTH	1/8"	99	49	33	24	20	16	14	12
	1/4"		24	20	12	10	8	7	6
	3/8"			11	8	6	5	5	4
	1/2"				6	5	4	3	3

* All values are approximations based on industry information and may vary significantly due to joint dimensions/configurations, porosity, substrate texture, installation technique, and waste — all factors beyond WeatherTek's control. WeatherTek is not liable for variances in linear footage or coverage. Always test a small area to determine actual material requirements.

Chemical & Physical Properties

Skin Time Internal Method	< 30 minutes @ 70°F / 50% RH
Tack Free Time Internal Method	< 60 minutes @ 70°F / 50% RH
Cure Rate Internal Method	1/4" Bead in 48 Hours
VOC EPA Method 24	< 28 g/L, less water and exempt solvents
100% Modulus of Elasticity ASTM D412	100 - 175 psi
Elongation @ Break ASTM D412	225-275%
Movement Capacity ASTM C719	±35%
Tensile Strength ASTM D412	180 - 230 psi
Sag/Slump ASTM D2202	Minimal; < 0.2"
UV Rating ASTM G154	No discoloration or change in appearance after 1000 hours
Density Internal Method	Approx. 12.7 lbs/gal
Water Penetration Resistance Around Nails ASTM D1970	Pass
Crack Bridging Ability ASTM C1305	Pass
Moisture Vapor Permeance ASTM E96 Procedure B	≥ 5 perms



Get Started Today

Visit weathertekbp.com to learn more about how WeatherTek can revolutionize your building projects. Contact us for samples or specifications.



PART OF THE WEATHERTEK SYSTEM

WeatherTek STP is eligible for a 20-Year WeatherTek System Warranty when installed with approved WeatherTek components.

Visit weathertekbp.com for details