



WeatherTek®

SEAM TAPE

PART OF THE WEATHERTEK SYSTEM



All-Weather Seaming for Professionals

WeatherTek Seam Tape is a high-performance seaming tape engineered for the rigorous demands of modern construction. Designed with a proprietary cold-weather acrylic adhesive and a durable polyester backing, this next-generation tape delivers unmatched bonding strength — even in extreme temperatures. Whether you're sealing house wrap, rigid insulation, or vapor barriers, ensures lasting protection and easy application.

Ideal For:

- Seaming house wraps and weather-resistant barriers
- Sealing joints in rigid foam insulation and sheathing
- General-purpose air and moisture sealing applications

PRODUCT CONSTRUCTION

Backing	PET film (1.5 mil) hand tearable
Adhesive	Acrylic (cold weather solvent acrylic)

TECHNICAL DATA

Total Thickness	3.38 mils
Tensile	20 lbs./in.
Adhesion	70 oz./in.
Application Temp	-4°F to 105°F (-20°C to 40°C)
Service Temp	-22°F to 148°F (-30°C to 120°C)

WVTR ASTM 96 DESICCANT METHOD

US Perms	Ng/Pa-s-m2	g/m2-day	g/100 in2-day
0.012	0.686	0.083	0.0054

Storage & Use:

Store in original packaging, out of sunlight, in a cool, dry place. Use within 12 months. Apply only to clean, dry, contaminant-free surfaces. Performance may vary by application.



UV & Temperature Stable

9 month UV exposure
Performs from -22°F to 148°F.
Sticks in temps as low as -4°F.



Strong Acrylic Bond

Grips hard-to-stick surfaces



Flexible & Hand Tearable

Applies easily, no tools needed.



Water Resistance

Protects against moisture and rain.

Sizes

48 mm x 50 yd.
72 mm x 50 yd.

Get Started Today

Visit weathertekbp.com to learn more about how WeatherTek can revolutionize your building projects. Contact us for samples or specifications.



PART OF THE WEATHERTEK SYSTEM

WeatherTek Seam Tape is eligible for a 20-Year WeatherTek System Warranty when installed with approved WeatherTek components.

Visit weathertekbp.com for details or call 904-877-9835